

Viking 30

10 year
warranty



JOSEF DAVIDSSONS
since 1882



Viking 30

Part. no: 100032001, top connection

Part. no: 100032002, rear connection

The timeless design with glazed hearth door and compact external dimensions makes the Viking 30 a focal point in both new and old kitchens. Only 5 cm light concrete is required as a firewall on each side of the range. The modern hearth, where the fuel is combusted by supplying secondary air via holes in the soapstone walls, provides the highest possible efficiency. The convection system ventilates the range while heating the room air. For newly built houses or for mechanical ventilation, the range is prepared for connection to the outdoor air. The handle in oak or stainless steel does not get hot during use. The chimney can be connected at the rear or at the top. The range is accompanied by stove hook, soot rake, ash box, stove black and heat-proof mortar. For rear connection, a chimney collar and flue connection are also included.

Accessories



Extension kit
Powder coated black
Gives the height 900-920 mm
Part. no: 100032860



Floor panel
Powder coated black
500x400 mm.
Part no: 990000501



Fan/Heat mover
Height 180mm
Blade width 180mm
Part. no: 990001026

10 year warranty



Technical data

| | | | |
|-----------------------------------|---------------|--|---------|
| Power (kW) | 6 | Weight (kg) | 140 |
| Efficiency (%) | 78 | Length of firewood (max mm) | 370 |
| Heating surface (m ²) | 30-70 | Approval Certificate | 0386/04 |
| Height (mm) | 850-900 (920) | Flue pipe dimension Ø (mm) | 125 |
| Depth (mm) | 600 | External air connection Ø (mm) | 65 |
| Width (mm) | 300 | Warranty (Not applicable to glass and replaceable fireplace details) | 10 år |

Dimensional drawing, mm

VIKING 30/JD 320

