EU Declaration of Conformity (DoC)

ManufacturerJosef Davidssons Eftr ABAddressJättevägen 1Emailinfo@josefdavidssons.seWebsitewww.josefdavidssons.seTelephone+46 371-20001





THE OBJECT OF THE DECLARATION DESCRIBED ABOVE IS IN CONFORMITY WITH THE RELEVANT UNION HARMONIZATION LEGISLATION (DIRECTIVE/S AND REGULATION/S)						
EU 2015/1185	EU 305/2011					
EU 2015/1186	EU 574/2014					
EU 2017/ 1369	EN 12815:2001/A1:2004					
EU 2009/125						

TECHNICAL DOCUMENTATION					
Indirect heating functionality	No				
Direct heat output	4,5 kW				
Energy Efficiency Index	110				
Test report	30-13639-T, NB 1015				

FUEL	PREFERRED FUEL	OTHER SUITABLE FUEL	η _s (%)	EMISSIONS AT NOMINAL HEAT OUTPUT			
				PM	ogc	со	NO _x
				mg/ Nm³ (13% O₂)			
Wood logs with moisture content ≤25%	YES	NO	72,8	21	105	1173	135
Compressed wood with moisture content <12%	NO	NO					
Other woody biomass	NO	NO					
Non-wood biomass	NO	NO					
Anthracite and dry steam coal	NO	NO					
Hard coke	NO	NO					
Low temperature coke	NO	NO					
Bituminous coal	NO	NO					
Lignite briquettes	NO	NO					
Peat briquettes	NO	NO					
Blended fossil fuel briquettes	NO	NO					
Other fossil fuel	NO	NO					
Blended biomass and fossil fuel briquettes	NO	NO					

CHARACTERISTICS WHEN OPERATING WITH THE PREFERRED FUEL								
ITEM	SYMBOL	VALUE	UNIT	TYPE OF HEAT OUTPUT/ROOM TEMPERATURE CONTROL				
HEAT OUTPUT	Single stage heat output, no room temperature control							
Nominal heat output	P _{nom}	4,5 kW	kW	Two or more manual stages, no room temperature control				
USEFUL EFFICIENCY, BASED ON NET CALORIFIC VALUE (NCV)	With mechanic thermostat room temperature control No							
Useful efficiency at nominal heat output	η _{th,nom}	82,8	%	With electronic room temperature control				
AUXILIARY ELECTRICITY CONSUMPTION	With electronic room temperature control plus day timer No							
At nominal heat output	el _{max}	-	kW	With electronic room temperature control plus week timer				
At minimum heat output	el _{min}	-	kW	OTHER CONTROL OPTIONS				
In standby mode	el _{SB}	-	kW	Room temperature control, with presence detection				
				Room temperature control, with open window detection	No			
				With distance control option				
Specific precautions for assembly, installation, or maintenance. Fire protection and safety distances to combustible building materials must be observed under all circumstances. A sufficient supply of combustion air must always be guaranteed. Air suction systems can interfere with the combustion air supply.								

The undersigned is responsible for the manufacture and conformity with the declared performance.

Mikael Andersson, Product manager, Josef Davidssons Eftr AB – Reftele, 2022-03-07