## EU Declaration of Conformity (DoC)

ManufacturerJosef Davidssons Eftr AB<br/>Jättevägen 1<br/>337 5 Reftele, SwedenEmailinfo@josefdavidssons.seWebsitewww.josefdavidssons.seTelephone+46 371-200 01



S ISSUED UNDER OUR SOLE RESPONSIBILITY FOR THE FOLLOWING PRODUCT:

Trade name Heimdall 790

## IDENTIFICATION OF PRODUCT





THE OBJECT OF THE DECLARATION DESCRIBED ABOVE IS IN CONFORMITY WITH THE RELEVANT UNION HARMONIZATION LEGISLATION (DIRECTIVE/S AND REGULATION/S)						
EU 2015/1185	EU 305/2011	EN 12815:2001/A1:2004/AC:2007				
EU 2015/1186	EU 574/2014	SS-EN 16510-2-3:2022				
EU 2017/ 1369	EU 2009/125					

TECHNICAL DOCUMENTATION				
Indirect heating functionality	No			
Direct heat output	5,7kW			
Energy Efficiency Index	116			
Test report	RISE 0100115-1200521-3			

FUEL	PREFERRED FUEL	OTHER SUITABLE FUEL	ηs (%)	EMISSIONS AT NOMINAL HEAT OUTPUT			
				PM	ogc	со	NO <sub>x</sub>
				mg/ Nm³ (13% O₂)			
Wood logs with moisture content ≤25%	YES	NO	70	33	113	1177	102
Compressed wood with moisture content <12%	NO	NO					
Other woody biomass	NO	NO					
Non-wood biomass	NO	NO					
Anthracite and dry steam coal	NO	NO					
Hard coke	NO	NO					
Low temperature coke	NO	NO					
Bituminous coal	NO	NO					
Lignite briquettes	NO	NO					
Peat briquettes	NO	NO					
Blended fossil fuel briquettes	NO	NO					
Other fossil fuel	NO	NO					
Blended biomass and fossil fuel briquettes	NO	NO					

CHARACTERISTICS WHEN OPERATING WITH THE PREFERRED FUEL							
ITEM	SYMBOL	VALUE	UNIT	TYPE OF HEAT OUTPUT/ROOM TEMPERATURE CONTROL			
HEAT OUTPUT			Single stage heat output, no room temperature control	No			
Nominal heat output	P <sub>nom</sub>	5,7 kW	kW	Two or more manual stages, no room temperature control			
USEFUL EFFICIENCY, BASED ON NET CALORIFIC VALUE (NCV)				With mechanic thermostat room temperature control	No		
Useful efficiency at nominal heat output	η <sub>th,nom</sub>	80	%	With electronic room temperature control			
AUXILIARY ELECTRICITY CONSUMPTION			With electronic room temperature control plus day timer	No			
At nominal heat output	el <sub>max</sub>	-	kW	With electronic room temperature control plus week timer			
At minimum heat output	el <sub>min</sub>	-	kW	OTHER CONTROL OPTIONS			
In standby mode	elsa	-	kW	Room temperature control, with presence detection	No		
			•	Room temperature control, with open window detection	No		
				With distance control option			
Specific precautions for assembly, installation, or maintenance.				building materials must be observed under all circumstances. A d. Air suction systems can interfere with the combustion air sup			

The undersigned is responsible for the manufacture and conformity with the declared performance.

Mikael Andersson, Product manager, Josef Davidssons Eftr AB – Reftele, 2024-02-01